

SFT – Technická data a nosnosti (pokračování)

Rozměr L/S5	Ráfek * (dovolený)	Šířka (mm)	Vnější průměr (mm)	Statický poloměr (mm)	Účinný obvod (mm)	Index obvodové rychlosti	Nosnost pneumatiky (kg) při hustici tlaku (bar)												Rychlost (km/h)
							0,4	0,6	0,8	1,0	1,2	1,4	1,6	2,0	2,4	2,8	3,2		
900/70 R 32 188 A8 (185 B)	DW 27 B DW 30 B	895 925	2 050	896	6 050	975	4 615	5 120	5 055	5 530	6 060	6 700	7 215	7 750	8 415	9 250	50		
							4 940	5 460	5 395	5 870	6 400	7 040	7 555	8 200	8 850	9 500	10 000	40	
							5 125	5 685	5 615	6 090	6 620	7 260	7 775	8 420	9 065	9 710	10 200	30	
							5 675	6 300	6 230	6 705	7 235	7 875	8 410	9 055	9 700	10 345	10 800	25	
							6 000	6 660	6 590	7 065	7 595	8 235	8 770	9 415	10 060	10 705	11 200	20	
1050/50 R 32 178 A8 (178 B)	36.00 VA	1 015	1 890	855	5 640	875	4 200	4 655	5 045	5 515	5 955	6 500	7 055	7 500	50				
							4 495	4 985	5 395	5 900	6 370	6 955	7 550	8 025	8 600	9 000	40		
							4 665	5 170	5 595	6 120	6 610	7 215	7 830	8 325	8 900	9 300	30		
							5 170	5 730	6 200	6 785	7 320	7 995	8 680	9 225	9 800	10 200	25		
							5 465	6 055	6 555	7 170	7 740	8 450	9 175	9 750	10 325	10 800	20		
1250/50 R 32 188 A8 (185 B)	44" 40"	1 220 1 180	2 020	890	6 000	975	4 730	5 020	5 655	6 265	6 960	7 750	8 500	9 250	50				
							5 060	5 905	6 645	7 265	8 185	9 095	9 995	10 700	11 400	12 000	40		
							5 250	6 125	6 895	7 640	8 490	9 435	10 370	11 100	11 800	12 400	30		
							5 815	6 785	7 640	8 470	9 410	10 455	11 490	12 300	13 000	13 600	25		
							6 620	7 725	8 695	9 640	10 710	11 900	13 075	14 000	15 445	16 520	20		
1250/50 R 32 194 A8 (191 B)	44" 40"	1 220 1 180	2 020	890	6 000	975	4 730	5 020	5 655	6 265	6 960	7 750	8 500	9 250	50				
							5 060	5 905	6 645	7 265	8 185	9 095	9 995	10 700	11 400	12 000	40		
							5 250	6 125	6 895	7 640	8 490	9 435	10 370	11 100	11 800	12 400	30		
							5 815	6 785	7 640	8 470	9 410	10 455	11 490	12 300	13 000	13 600	25		
							6 620	7 725	8 695	9 640	10 710	11 900	13 075	14 000	15 445	16 520	20		
650/60 R 34 159 D (162 A8)	DW 20 B DW 21 B DW 23 B	650 660 680	1 638	740	4 935	775	2 430	2 645	3 055	3 355	3 650	4 040	4 375	50					
							2 550	2 755	3 060	3 345	3 675	4 000	4 420	4 750	40				
							3 105	2 895	3 215	3 515	3 860	4 200	4 645	5 030	5 300	30			
							3 315	3 525	3 915	4 280	4 700	5 110	5 655	6 125	6 565	20			
							3 660	3 875	4 265	4 640	5 050	5 465	5 915	6 390	6 825	10			
650/65 R 34 161 D (164 A8)	DW 20 B DW 21 B DW 23 B	664 674 694	1 719	769	5 116	825	2 850	3 070	3 215	3 475	3 690	3 875	4 305	4 625	65				
							2 995	3 205	3 375	3 645	3 875	4 070	4 520	4 855	5 000	50			
							3 365	3 520	3 800	4 040	4 250	4 710	5 000	5 400	5 700	40			
							4 095	3 365	3 695	3 995	4 245	4 455	4 950	5 320	5 625	30			
							4 645	4 095	4 500	4 860	5 165	5 425	6 025	6 475	6 825	20			
710/60 R 34 164 D (167 A8)	DW 23 B	700	1 700	770	5 060	825	2 785	3 030	3 205	3 505	3 820	4 125	4 500	65					
							2 925	3 160	3 365	3 680	4 010	4 300	4 855	5 250	5 500	50			
							3 560	3 810	4 035	4 385	4 715	5 060	5 450	5 850	6 200	40			
							3 760	4 010	4 235	4 585	4 915	5 260	5 650	6 050	6 400	30			
							4 050	4 300	4 525	4 875	5 205	5 550	5 940	6 340	6 700	20			
650/65 R 38 157 D (160 A8)	W 18 L DW 20 B DW 21 B	645 660 670	1 828	810	5 445	875	3 000	3 230	3 380	3 655	3 905	4 125	50						
							3 150	3 370	3 550	3 835	4 100	4 330	4 595	4 800	40				
							3 835	3 370	3 705	4 000	4 275	4 500	4 745	5 000	5 200	30			
							4 310	3 540	3 890	4 200	4 490	4 745	5 000	5 255	5 500	20			
							4 735	4 310	4 735	5 115	5 465	5 775	6 190	6 605	6 950	10			
650/75 R 38 169 D (172 A8)	DW 21 B DW 20 B DW 23 B	667 657 687	1 944	872	5 795	925	3 445	3 760	3 990	4 375	4 645	4 875	5 425	5 800	65				
							3 620	3 920	4 190	4 590	4 880	5 120	5 695	6 090	6 300	50			
							4 405	3 920	4 370	4 790	5 085	5 300	5 940	6 300	6 600	40			
							4 620	4 120	4 590	5 030	5 340	5 605	6 235	6 670	7 000	30			
							5 015	4 585	5 065	5 505	5 815	6 085	6 720	7 150	7 500	20			
650/85 R 38 173 D (176 A8)	DW 23 B DW 20 B DW 21 B	720 688 699	2 070	920	6 130	975	3 855	4 210	4 465	4 895	5 195	5 450	6 075	6 500	65				
							4 050	4 690	5 140	5 455	5 725	6 375	6 825	7 275	7 600	50			
							4 930	4 310	4 830	5 185	5 500	5 960	6 360	6 800	7 100	40			
							5 610	4 610	5 135	5 630	5 975	6 270	6 985	7 475	7 800	30			
							6 250	5 610	6 250	6 855	7 275	7 630	8 500	9 100	9 500	20			
710/70 R 38 166 D (169 A8)	DW 23 B DW 25 B	736 756	1 958	870	5 780	925	3 715	4 055	4 305	4 720	5 030	5 300	65						
							3 905	4 230	4 520	4 955	5 280	5 565	6 095	6 500	6 800	50			
							4 445	4 715	5 170	5 510	5 800	6 095	6 625	7 050	7 300	40			
							4 750	4 445	4 950	5 425	5 785	6 095	6 625	7 050	7 300	30			
							5 410	4 605	5 115	5 605	5 945	6 255	6 785	7 210	7 500	20			
710/70 R 38 171 D (174 A8)	DW 23 B DW 25 B	736 756	1 958	870	5 780	925	3 715	4 055	4 305	4 720	5 030	5 300	65						
							3 905	4 230	4 520	4 955	5 280	5 565	6 095	6 500	6 800	50			
							4 445	4 715	5 170	5 510	5 800	6 095	6 625	7 050	7 300	40			
							4 750	4 445	4 950	5 425	5 785	6 095	6 625	7 050	7 300	30			
							5 410	4 605	5 115	5 605	5 945	6 255	6 785	7 210	7 500	20			
800/70 R 38 173 D (176 A8)	DW 25 B DW 27 B	765 787	2 052	911	6 090	975	4 480	4 890	5 190	5 690	6 070	6 500	65						
							4 705	5 100	5 685	6 230	6 650	7 100	7 500	7 800	50				
							5 360	5 360	5 970	6 545	6 980	7 360	7 800	8 100	40				
							5 730	5 325	5 970	6 545	6 980	7 360	7 800	8 100	30				
							6 525	5 730	6 345	6 960	7 580	8 190	8 800	9 100	20				
800/70 R 38 178 D (181 A8)	DW 25 B DW 27 B	765 787	2 052	911	6 090	975	4 480	4 890	5 190	5 690	6 070	6 500	65						
							4 705	5 100	5 685	6 230	6 650	7 100	7 500	7 800	50				
							5 360	5 360	5 970	6 545	6 980	7 360	7 800	8 100	40				
							5 730	5 325	5 970	6 545	6 980	7 360	7 800	8 100	30				
							6 525	5 730	6 345	6 960	7 580	8 190	8 800	9 100	20				
900/60 R 38 172 D (175 A8)	DW 27 B DW 30 B	870 900	2 060	918	6 115	975	4 235	4 610	4 875	5 325	5 825	6 300	65						
							4 450	4 805	5 120	5 595	6 115	6 615	7 095	7 500	50				
							5 415	4 805	5 340	5 835	6 375	6 900	7 450	7 850	40				
							6 145	4 450	5 050	5 605	6 125	6 695	7 245	7 650	30				
							6 825	4 610	5 205	5 760	6 280	6 830	7 380	7 800	20				
900/60 R 38 178 D (181 A8)	DW 27 B DW 30 B	870 900	2 060	918	6 115	975	4 235	4 610	4 875	5 325	5 825	6 300	65						
							4 450	4 805	5 120	5 595	6 115	6 615	7 095	7 500	50				
							5 415	4 805	5 340	5 835	6 375	6 900	7 450	7 850	40				
							6 145	4 450	5 050	5 605	6 125	6 695	7 245	7 650	30				
							6 825	4 610	5 205	5 760	6 280	6 830	7 380	7 800	20				
580/85 R 42 163 D (166 A8)	W 18 L DW 20 B DW 21 B	567 587 597	2 045	920	6 100	975	3 125	3 405	3 605	3 945	4 405	4 875	65						
							3 285	3 550	3 785	4 140	4 630	5 120	5 600	6 000	50				
							3 995	3 730	4 145	4 535	5 070	5 605	6 085	6 500	40				
							4 540	3 405	3 815	4 225	4 635	5 045	5 455	5 865	30				
							5 050	3 995	4 405	4 815	5 225	5 635	6 045	6 455	20				

SFT – Technická data a nosnosti (pokračování)

Rozměr L/S5	Ráfek * (dovolený)	Šířka (mm)	Vnější průměr (mm)	Statický poloměr (mm)	
-------------	--------------------	------------	--------------------	-----------------------	--

