



AGRITERRA

Tires for transport equipment

Mitas

mitas-tires.com



Discover our website



Discover our mobile app



Follow us



© TWS CZ: 10/22_1 | Subject to technical amendments, printing errors and mistakes in text or illustrations



Mitas

Mitas

AGRITERRA

Fast and powerful trailer tires for wide range of applications such as trailers, loading and transport vehicles, spreaders and slurry tankers.



AGRITERRA 02	
LOAD CAPACITY	●●●●
ROAD PERFORMANCE	●●●●
FIELD PERFORMANCE	●●●●●
SELF-CLEANING	●●●●
RESISTANCE	●●●●



AGRITERRA 03	
LOAD CAPACITY	●●●●
ROAD PERFORMANCE	●●●●●
FIELD PERFORMANCE	●●●●●
SELF-CLEANING	●●●●●
RESISTANCE	●●●●



AGRITERRA 04	
LOAD CAPACITY	●●●●
ROAD PERFORMANCE	●●●●
FIELD PERFORMANCE	●●●●●
SELF-CLEANING	●●●●●
RESISTANCE	●●●●

Tread pattern application

AGRITERRA 02 – gentle to **grassland** due to rounded shoulder and high positive share.

AGRITERRA 03 – excellent self-cleaning properties due to large space between the lugs. Suitable for **on-road application**.

AGRITERRA 04 – ideal for **wet terrain** due to rounded shoulder and the large space between the lugs.

Key product features



High load capacity due to high volume of tire.



Construction with **hexa-bead core for outstanding fit**, even at low air pressures, therefore released for tire inflation systems.



Steel belt under the tread for high speed capability and long lifetime.



Reduced noise emission and vibration due to innovative tread design, quiet on the road.



Excellent cost efficiency due to low rolling resistance and high load capacity.



Agriterra tires are suitable for **wide range of applications** such as trailers, loading and transport vehicles, spreaders and slurry tankers.

AGRITERRA

Technical data

Tire size	Tread pattern	Service description LI/SS	Rims* (permitted)	Section width (mm)	Overall diameter (mm)	Loaded static radius (mm)	Rolling circumference (mm)	Tire pressure (bar)	Tire load capacity (kg)	Speed (km/h)
500/60 R 22.5 IMP	AGRITERRA 02	161 D	AG 16.00×22.5 15.00×22.5 16.00×22.5 17.00×22.5	524	1 172	543	3 547	6.0	4 625	65
560/45 R 22.5 IMP	AGRITERRA 02	152 D	AG 16.00×22.5	564	1 076	495	3 228	4.0	3 550	65
560/45 R 22.5 IMP	AGRITERRA 02	160 D	AG 16.00×22.5	551	1 080	498	3 261	6.0	4 500	65
560/60 R 22.5 IMP	AGRITERRA 02	165 D	AG 16.00×22.5 AG 20.00×22.5 16.00×22.5 17.00×22.5	567 607	1 247	568	3 743	5.0	5 150	65
VF 560/60 R 22.5 IMP	AGRITERRA 02 SP	166 D	AG 16.00×22.5 AG 20.00×22.5	570 610	1 245	550	3 685	3.2	5 300	65
600/50 R 22.5 IMP	AGRITERRA 02	163 D	AG 20.00×22.5	631	1 173	537	3 530	5.0	4 875	65
600/50 R 22.5 IMP	AGRITERRA 02	167 D	AG 20.00×22.5	631	1 173	537	3 530	6.0	5 450	65
620/40 R 22.5 IMP	AGRITERRA 02	158 D	AG 20.00×22.5	605	1 070	490	3 220	5.0	4 250	65
710/45 R 22.5 IMP	AGRITERRA 02	165 D	AG 24.00×22.5 AG 20.00×22.5	729	1 208	545	3 610	4.0	5 150	65
620/75 R 26 IMP	AGRITERRA 02	169 D	DW 20 B×26 DW 18 B×26 DW 21 B×26	625 605 635	1 590	710	4 730	3.2	5 800	65
600/55 R 26.5 IMP	AGRITERRA 02	165 D	AG 20.00×26.5	626	1 335	585	4 033	4.0	5 150	65
650/55 R 26.5 IMP	AGRITERRA 02	169 D	AG 20.00×26.5	653	1 383	627	4 142	4.0	5 800	65
650/65 R 26.5 IMP	AGRITERRA 02	174 D	AG 20.00×26.5	675	1 516	683	4 527	4.0	6 700	65
710/50 R 26.5 IMP	AGRITERRA 02	170 D	AG 24.00×26.5 AG 20.00×26.5	737	1 388	628	4 189	4.0	6 000	65
800/45 R 26.5 IMP	AGRITERRA 02	174 D	AG 24.00×26.5 AG 28.00×26.5	770	1 394	628	4 163	4.0	6 700	65
600/60 R 30.5 IMP	AGRITERRA 04	173 D	AG 20.00×30.5	625	1 500	690	4 524	5.0	6 500	65
680/60 R 30.5 IMP replaces 650/65 R 30.5	AGRITERRA 03	176 D	AG 20.00×30.5	697	1 623	740	4 875	4.0	7 100	65
710/50 R 30.5 IMP	AGRITERRA 02	173 D	AG 24.00×30.5 AG 20.00×30.5	720 680	1 488	680	4 475	4.0	6 500	65
750/60 R 30.5 IMP	AGRITERRA 03	181 D	AG 24.00×30.5	792	1 672	755	4 998	4.0	8 250	65
850/50 R 30.5 IMP	AGRITERRA 02	182 D	AG 28.00×30.5	880	1 620	732	4 844	4.0	8 500	65
800/65 R 32 IMP	AGRITERRA 04	185 D	DW 25 B×32 DW 23 B×32 DW 27 B×32 DW 28 B×32	785 765 805 815	1 859	835	5 442	3.6	9 250	65

* Additional permitted rims may be available on request
Complete technical details you can find on www.mitas-tires.com or in the Mitas technical catalogue.
Tubeless tires – may be used with a tube.