



**AGRITERRA**

Tires for transport equipment

**Mitas**

mitas-tires.com



Discover our website



Discover our mobile app



Follow us



© Yokohama TWS 6/23\_1 | Subject to technical amendments, printing errors and mistakes in text or illustrations



**Mitas**

**Mitas**

## AGRITERRA

Fast and powerful trailer tires for wide range of applications such as trailers, loading and transport vehicles, spreaders and slurry tankers.



AGRITERRA 02	
LOAD CAPACITY	●●●●
ROAD PERFORMANCE	●●●●
FIELD PERFORMANCE	●●●●●
SELF-CLEANING	●●●●
RESISTANCE	●●●●



AGRITERRA 03	
LOAD CAPACITY	●●●●
ROAD PERFORMANCE	●●●●●
FIELD PERFORMANCE	●●●●
SELF-CLEANING	●●●●●
RESISTANCE	●●●●



AGRITERRA 04	
LOAD CAPACITY	●●●●
ROAD PERFORMANCE	●●●●
FIELD PERFORMANCE	●●●●●
SELF-CLEANING	●●●●●
RESISTANCE	●●●●

## Tread pattern application

**AGRITERRA 02** – gentle to **grassland** due to rounded shoulder and high positive share.

**AGRITERRA 03** – excellent self-cleaning properties due to large space between the lugs. Suitable for **on-road application**.

**AGRITERRA 04** – ideal for **wet terrain** due to rounded shoulder and the large space between the lugs.

## Key product features



**High load capacity** due to high volume of tire.



Construction with **hexa-bead core for outstanding fit**, even at low air pressures, therefore released for tire inflation systems.



**Steel belt** under the tread for high speed capability and long lifetime.



**Reduced noise emission and vibration** due to innovative tread design, quiet on the road.



**Excellent cost efficiency** due to low rolling resistance and high load capacity.



Agriterra tires are suitable for **wide range of applications** such as trailers, loading and transport vehicles, spreaders and slurry tankers.

## AGRITERRA Technical data

Tire size	Tread pattern	Service description LI/SS	Rims* (permitted)	Section width (mm)	Overall diameter (mm)	Loaded static radius (mm)	Rolling circumference (mm)	Tire pressure (bar)	Tire load capacity (kg)	Speed (km/h)
<b>500/60 R 22.5 IMP</b>	AGRITERRA 02	161 D	AG 16.00×22.5 15.00×22.5 16.00×22.5 17.00×22.5	524	1 172	543	3 547	6.0	4 625	65
<b>560/45 R 22.5 IMP</b>	AGRITERRA 02	152 D	AG 16.00×22.5	564	1 076	495	3 228	4.0	3 550	65
<b>560/45 R 22.5 IMP</b>	AGRITERRA 02	160 D	AG 16.00×22.5	551	1 080	498	3 261	6.0	4 500	65
<b>560/60 R 22.5 IMP</b>	AGRITERRA 02	165 D	AG 16.00×22.5 AG 20.00×22.5 16.00×22.5 17.00×22.5	567 607	1 247	568	3 743	5.0	5 150	65
<b>VF 560/60 R 22.5 IMP</b>	AGRITERRA 02 SP	166 D	AG 16.00×22.5 AG 20.00×22.5	570 610	1 245	550	3 685	3.2	5 300	65
<b>600/50 R 22.5 IMP</b>	AGRITERRA 02	163 D	AG 20.00×22.5	631	1 173	537	3 530	5.0	4 875	65
<b>600/50 R 22.5 IMP</b>	AGRITERRA 02	167 D	AG 20.00×22.5	631	1 173	537	3 530	6.0	5 450	65
<b>620/40 R 22.5 IMP</b>	AGRITERRA 02	158 D	AG 20.00×22.5	605	1 070	490	3 220	5.0	4 250	65
<b>710/45 R 22.5 IMP</b>	AGRITERRA 02	165 D	AG 24.00×22.5 AG 20.00×22.5	729	1 208	545	3 610	4.0	5 150	65
<b>620/75 R 26 IMP</b>	AGRITERRA 02	169 D	DW 20 B×26 DW 18 B×26 DW 21 B×26	625 605 635	1 590	710	4 730	3.2	5 800	65
<b>600/55 R 26.5 IMP</b>	AGRITERRA 02	165 D	AG 20.00×26.5	626	1 335	585	4 033	4.0	5 150	65
<b>650/55 R 26.5 IMP</b>	AGRITERRA 02	169 D	AG 20.00×26.5	653	1 383	627	4 142	4.0	5 800	65
<b>650/65 R 26.5 IMP</b>	AGRITERRA 02	174 D	AG 20.00×26.5	675	1 516	683	4 527	4.0	6 700	65
<b>710/50 R 26.5 IMP</b>	AGRITERRA 02	170 D	AG 24.00×26.5 AG 20.00×26.5	737	1 388	628	4 189	4.0	6 000	65
<b>800/45 R 26.5 IMP</b>	AGRITERRA 02	174 D	AG 24.00×26.5 AG 28.00×26.5	770	1 394	628	4 163	4.0	6 700	65
<b>600/60 R 30.5 IMP</b>	AGRITERRA 04	173 D	AG 20.00×30.5	625	1 500	690	4 524	5.0	6 500	65
<b>680/60 R 30.5 IMP</b> replaces 650/65 R 30.5	AGRITERRA 03	176 D	AG 20.00×30.5	697	1 623	740	4 875	4.0	7 100	65
<b>710/50 R 30.5 IMP</b>	AGRITERRA 02	173 D	AG 24.00×30.5 AG 20.00×30.5	720 680	1 488	680	4 475	4.0	6 500	65
<b>750/60 R 30.5 IMP</b>	AGRITERRA 03	181 D	AG 24.00×30.5	792	1 672	755	4 998	4.0	8 250	65
<b>850/50 R 30.5 IMP</b>	AGRITERRA 02	182 D	AG 28.00×30.5	880	1 620	732	4 844	4.0	8 500	65
<b>800/65 R 32 IMP</b>	AGRITERRA 04	185 D	DW 25 B×32 DW 23 B×32 DW 27 B×32 DW 28 B×32	785 765 805 815	1 859	835	5 442	3.6	9 250	65

\* Additional permitted rims may be available on request  
Complete technical details you can find on [www.mitas-tires.com](http://www.mitas-tires.com) or in the Mitas technical catalogue.  
Tubeless tires – may be used with a tube.