

FL-08

Bias pneumatic – medium intensity applications

Material Handling Diagonal Tyres



Mitas FL-08

Strives to deliver optimum performances for medium intensity applications.

Key product features

Block tread design – Improve traction performance

Enhanced stability – Pattern specifically designed to improve directional stability


Shock absorbance – Heavy duties service



STABILITY



TYRE LIFE



COOL RUNNING

Technical data and load capacities

Tyre size (Alternative size)	Type	Rim (permitted)	Section width (mm)	Overall diameter (mm)	Minimal dual spacing (mm)	Tread depth (mm)	Service description L/SS	Ply Rating	Tyre load capacity (kg)		Tyre pressure (bar)
									Load wheel	Steering wheel	
4.00-8	TT	3 1/4I-8	112	414	138	6	94 A5 97 A5	8 PR 10 PR	870 950	670 730	9.00 10.00
NEW 15x4.5-8	TT	3.00D-8	117	381	140	8	100 A5	12 PR	1 040	800	10.00
5.00-8	TT	3.00D-8	132	467	158	11	106 A5 111 A5	8 PR 10 PR	1 235 1 415	950 1 090	8.25 10.00
16x6-8 (150/75-8)	TT	4.33R-8	152	425	175	12	113 A5	16 PR	1 495	1 150	10.00
18x7-8 (180/70-8)	TT	4.33R-8	173	462	199	14	121 A5 125 A5	14 PR 16 PR	1 885 2 145	1 450 1 650	9.00 10.00
6.00-9	TT	4.00E-9	160	540	192	13	118 A5 121 A5	10 PR 12 PR	1 715 1 885	1 320 1 450	8.50 10.00
21x8-9 (200/75-9)	TT	6.00E-9	200	535	230	15	134 A5	16 PR	2 755	2 120	10.00
6.50-10	TT	5.00F-10 (5.50F-10)	177	588	212 (218)	14	122 A5 125 A5 128 A5	10 PR 12 PR 14 PR	1 950 2 145 2 340	1 500 1 650 1 800	7.75 9.00 10.00
NEW 7.50-10	TT	5.00F-10	205	643	242	15	133 A5	12 PR	2 680	2 060	8.00
23x9-10 (225/75-10)	TT	6.50F-10	225	595	259	16	142 A5	20 PR	3 340	2 650	10.00
7.00-12	TT	5.00S-12	192	672	230	15	133 A5 134 A5 136 A5	12 PR 14 PR 16 PR	2 680 2 755 2 910	2 060 2 120 2 240	8.50 9.00 10.00
NEW 23x10-12	TT	8.00G-12	243	594	293	20	139 A5	16 PR	3 160	2 430	8.00
27x10-12 (250/75-12)	TT	8.00G-12	261	681	293	18	143 A5 146 A5 152 A5	14 PR 16 PR 20 PR	3 545 3 900 4 615	2 725 3 000 3 550	7.00 8.00 10.00
NEW 7.00-15	TT	5.50-15	198	748	236	17	140 A5	14 PR	3 250	2 500	9.25
7.50-15	TT	6.0-15 (6.5-15)	212	772	254 (260)	21	144 A5 146 A5	14 PR 16 PR	3 640 3 900	2 800 3 000	9.25 10.00
8.15-15 (28x9-15)	TT	7.0-15	216	707	248	18	146 A5	14 PR	3 900	3 000	10.00
8.25-15	TT	6.5-15	234	836	281	23	153 A5	18 PR	4 745	3 650	10.00
250-15 (250/70-15)	TT	7.50-15	250	735	288	20	153 A5 155 A5	18 PR 20 PR	4 745 5 040	3 650 3 875	9.50 10.00
NEW 28x12.5-15	TT	9.75-15	274	727	326	17	140 A5	20 PR	3 250	2 430	9.00
300-15 (315/70-15)	TT	8.00-15	300	840	345	23	165 A5	22 PR	6 695	5 150	10.00

© TWS CZ: 03/2020 // MagiC7 | Subject to technical amendments, printing errors and mistakes in text or illustrations

Mitas

mitas-tyres.com