

# Agricultural Tires



THE SMART PARTNER FOR YOUR SUCCESS

# Mitas

Tractor radial tires



## HC 2000

VF tire – Very High Flexion for high-horsepower tractors

- Lower inflation pressure provides excellent traction efficiency.
- Better ground protection due to reduced soil compaction.
- Higher load capacity for higher haulage efficiency.

Available sizes			
VF 420/85 R 28	151D	VF 480/70 R 38	172D
VF 540/65 R 30	155D	VF 520/85 R 42	174B
VF 540/65 R 30	161D	VF 650/65 R 42	170D
VF 600/70 R 30	165D	VF 710/70 R 42	179D
VF 380/85 R 34	149D	VF 480/80 R 46	164D
VF 420/85 R 34	154D	VF 480/80 R 46	175D
VF 540/65 R 34	163D	VF 480/95 R 50	170B
VF 380/95 R 38	154B	VF 380/105 R 54	168B

Tractor radial tires



## SFT – Super Flexion Tire

Maximum load capacity and traction

- Developed specifically for use on high-horsepower tractors.
- Gentle ground handling for higher yields.
- Maximum traction and outstanding productivity.

Available sizes				
620/75 R 26 166A8	600/70 R 30 152D	650/75 R 38 169D	650/75 R 42	165D
750/65 R 26 166D	620/75 R 30 166D	650/85 R 38 173D	680/80 R 42	180D
750/65 R 26 171D	710/55 R 30 159D	710/70 R 38 166D	710/70 R 42	173D
540/65 R 28 142D	710/60 R 30 162D	710/70 R 38 171D	710/75 R 42	175D
600/65 R 28 154D	750/55 R 30 162D	800/70 R 38 173D	IF 900/60 R 42 CFO	192A8
600/65 R 28 160D	650/60 R 34 159D	800/70 R 38 178D	900/60 R 42	180D
600/70 R 28 157D	650/65 R 34 161D	900/60 R 38 172D	IF 710/65 R 46	183D
600/70 R 28 161D	710/60 R 34 164D	900/60 R 38 178D	710/65 R 46	174D
540/65 R 30 150D	650/65 R 38 157D	580/85 R 42 163D		

Tractor radial tires



## SST – Silent Speed Tire

Noise-reducing radial tire for fast, comfortable and quiet road use

- Noise reduction of up to 6 dB(A) in the cab maximises concentration and minimises stress.
- Reduced rolling resistance, long tire life and high damage resistance.
- Highest possible sustained speed capability of up to 70 km/h.

Available sizes	
600/65 R 38	153D
650/65 R 38	157D
710/70 R 38	171D
650/65 R 42	165D
710/70 R 42	173D
710/75 R 42	175D

Tractor radial tires



## AC 65

Powerful wide tire for all-round applications

- Gentle ground handling in the field and on grassland.
- Comfortable on the road at high speeds up to 65 km/h.
- Very high transportation capability through large volume of air.
- Extremely economical due to excellent traction and low-wear tread compound.

Available sizes			
320/65 R 16	117D	540/65 R 28	142D
420/65 R 20	125D	600/65 R 28	147D
440/65 R 24	128D	540/65 R 30	150D
480/65 R 24	133D	600/65 R 30	149D
540/65 R 24	140D	540/65 R 34	145D
540/65 R 24	146D	600/65 R 34	151D
440/65 R 28	131D	600/65 R 34	157D
480/65 R 28	136D	540/65 R 38	147D
600/65 R 38	153D		
650/65 R 38	157D		
650/65 R 38	166D		
650/65 R 38	173D		
710/70 R 38	166D		
650/65 R 42	165D		

Tractor radial tires



## HC 70

The all-round benchmark in the 70 series wide tire segment

- Higher load capacity than conventional 70 series.
- Gentle handling of the soil due to rounded shoulders and lug design.
- Wide tire shoulders provide comfortable and safe road performance.
- Low operating costs due to minimised slip.

Available sizes		
320/70 R 24	116D	420/70 R 28
360/70 R 24	122D	480/70 R 28
320/85 R 24	122A8	420/85 R 34
340/85 R 24	125A8	420/85 R 34
380/85 R 24	131A8	480/70 R 30
420/70 R 24	130D	480/70 R 30
480/70 R 24	138D	480/70 R 30
380/70 R 28	127D	480/70 R 34
420/70 R 28	133D	
480/70 R 28	140D	
420/70 R 30	134D	
480/70 R 30	141D	
480/70 R 30	152D	
480/70 R 34	143D	
480/70 R 34	145D	
520/70 R 34	148D	
480/70 R 38	145D	
520/70 R 38	150D	
580/70 R 38	155D	

Tractor radial tires



## AC 85

Modern all-round standard tire for all applications

- Radial tire with balanced characteristics for a wide range for applications both on the field and on the road.
- Larger ground contact area makes the tire well suited for handling grassland.
- Long service life due to wear-resistant tread compound.

Available sizes									
280/85 R 20	112A8	280/85 R 28	118A8	420/90 R 30	147A8	380/80 R 38	142A8	520/85 R 42	162A8
320/85 R 20	119A8	320/85 R 28	124A8	460/85 R 30	145A8	380/95 R 38	147D	520/85 R 42	170A8
280/85 R 24	115A8	340/85 R 28	127A8	380/85 R 34	146A8	420/85 R 38	144A8	480/80 R 46	158A8
320/85 R 24	122A8	380/85 R 28	133A8	420/85 R 34	142A8	460/85 R 38	149A8	520/85 R 46	158A8
340/85 R 24	125A8	420/85 R 28	139A8	420/85 R 34	147A8	520/85 R 38	155A8	380/90 R 50	151A8
380/85 R 24	131A8	380/85 R 30	135A8	460/85 R 34	147A8	520/85 R 38	169A8	480/80 R 50	159A8
420/85 R 24	137A8	420/85 R 30	140A8	340/85 R 38	133A8	480/80 R 42	151A8	480/95 R 50	164D



## HC 1000

VF tire – Very High Flexion for self-propelled sprayers

- More lugs provide better durability, longer service life and lower operation cost.
- Higher maximum speed (65 km/h) for less time on the road.
- Reduced soil compaction for higher loads due to lower inflation pressure.

Available sizes			
VF 650/65 R 38 NRO	180D	VF 270/95 R 48	155D
VF 380/90 R 46	173D	VF 380/105 R 50	176D
VF 380/90 R 46	176D	VF 480/80 R 50	181D
VF 750/60 R 46 NRO	189D	VF 320/105 R 54	169D

NRO (Narrow Rim Option): The tire can also be used on a narrower rim than the standard rim.



Pic.: HC 3000

## HC 3000 & HC 3000 R

VF harvester tire – Very High Flexion for Cyclic Field Operation – CFO

- Less inflation pressure provides excellent traction efficiency.
- Higher load capacity for higher haulage efficiency.
- Larger footprint for better ground protection and reduced soil compaction.

Available sizes			
VF 750/65 R 26 CFO	180B	VF 520/85 R 42 CFO	177B
VF 1000/65 R 32 CFO	200A8*	VF 580/85 R 42 CFO	183B
VF 580/80 R 34 CFO	178B	VF 710/70 R 42 CFO	190B
VF 800/70 R 38 CFO	193B	VF 710/70 R 42 CFO	193B

\* Tread pattern HC 3000 R (R = Rounded Shoulder)



## SFT CHO – Cyclic Harvesting Operation

More load at lower tire pressure

- Maximum load capacity for Cyclic Harvesting Operation.
- Minimum inflation pressure during cyclic harvest operation.
- Good driving stability in road application.
- Reduces soil compaction due to a large footprint.
- Fulfills all legal requirements (limited vehicle width).

Available sizes					
680/85 R 32 CHO	178A8*	1050/50 R 32 CHO	184A8	900/60 R 38 CHO	181D
800/70 R 32 CHO	175A8	1250/50 R 32 CHO	194A8	680/80 R 42 CHO	180D
900/60 R 32 CHO	176A8	680/80 R 38 CHO	179D	800/70 R 42 CHO	182D
900/70 R 32 CHO	182A8	800/70 R 38 CHO	178D	900/60 R 42 CHO	183D
900/70 R 32 CHO	188A8	800/70 R 38 CHO	181D		

\* Tread pattern AC 70 G



Pic.: SFT

## SFT, AC 70 H/G/N & AC 75 G

Economical tire for gentle ground handling on harvesters

- Harvester tire with high load capacity and low inflation pressure.
- Wide and even distribution of ground pressure minimises pressure on the soil resistance.
- Low vibration on the road.
- High mileage performance.

Available sizes SFT			AC 70 H/G/N & AC 75 G		
1000/50 R 25	178A8	1250/50 R 32	188A8	650/75 R 32	167 A8 <sup>2</sup>
620/75 R 26	166B	1250/50 R 32	194A8	650/75 R 32	167 A8 <sup>1</sup>
620/75 R 30	166D	900/60 R 38	178D	IF 650/75 R 32 CFO	176 A8 <sup>1</sup>
800/70 R 32	175A8	580/85 R 42	163D	650/75 R 32	172 A8 <sup>3</sup>
900/60 R 32	176A8	580/85 R 42	168D	680/85 R 32	178 A8 <sup>3</sup>
900/60 R 32	181A8	680/80 R 42	180D	800/65 R 32	172 A8 <sup>2</sup>
900/70 R 32	188A8	IF 900/60 R 42 CFO	192A8	800/65 R 32	178 A8 <sup>4</sup>
1050/50 R 32	178A8				

<sup>1</sup> AC 75 G; <sup>2</sup> AC 70 H; <sup>3</sup> AC 70 G; <sup>4</sup> AC 70 N



Pic.: AGRITERRA 02

## AGRITERRA 02, 02 SP, 02 HD, 03 & 04

Fast and powerful trailer tires for wide range of applications

- High load capacity due to high volume of tire.
- Steel belt under the tread for high speed capability and long lifetime.
- Excellent cost efficiency due to low rolling resistance.

Available sizes AGRITERRA 02			AGRITERRA 03 & 04		
500/60 R 22.5 IMP	161D	710/45 R 22.5 IMP	165D	600/60 R 30.5 IMP	173D <sup>4</sup>
560/45 R 22.5 IMP	152D	600/55 R 26.5 IMP	165D	680/60 R 30.5 IMP	176D <sup>3</sup>
560/45 R 22.5 IMP	160D	650/55 R 26.5 IMP	169D	750/60 R 30.5 IMP	181D <sup>3</sup>
560/60 R 22.5 IMP	165D	650/65 R 26.5 IMP	174D	800/65 R 32 IMP	185D <sup>4</sup>
VF 560/60 R 22.5 IMP	166D <sup>1</sup>	710/50 R 26.5 IMP	170D		
560/60 R 22.5 IMP	169D <sup>2</sup>	800/45 R 26.5 IMP	174D		
600/50 R 22.5 IMP	163D	710/50 R 30.5 IMP	173D		
600/50 R 22.5 IMP	167D	850/50 R 30.5 IMP	182D		
620/40 R 22.5 IMP	158D				

<sup>1</sup> AGRITERRA 02 SP; <sup>2</sup> AGRITERRA 02 HD

<sup>3</sup> AGRITERRA 03; <sup>4</sup> AGRITERRA 04



## HCM – High Capacity Municipal

All-purpose quiet-running tire for all terrains and applications

- Particularly suitable for municipal and road maintenance tractors and equipment. Designed for all-season use.
- High durability due to steel belted radial construction and unique design within its central area.
- Exceptional traction characteristics due to an innovative lug, designed to increase grip on a wide range of surfaces.

Available sizes					
340/80 R 18 IND	138D	360/80 R 28 IND	141D	440/80 R 34 IND	155D
360/80 R 20 IND	143D	440/80 R 28 IND	151D	480/80 R 34 IND	159D
360/80 R 24 IND	139D	440/80 R 30 IND	153D	480/80 R 38 IND	161D
400/80 R 24 IND	144D	400/80 R 28 IND	146D	540/80 R 38 IND	167D
440/80 R 24 IND	149D	540/65 R 30 IND	156D	650/65 R 42 IND	171D



Discover our website



Discover our mobile app



Follow us



Yokohama TWS Czech Republic a.s.  
Švehlova 1900/3, 106 00 Prague 10  
Czech Republic